



More information on the website
radwag.com/en/info,w1,9FZ

PM01.EX-1 Intrinsically Safe Power Supply Intended for Ex Scale



The drawings, photos and graphics used are for illustrative purposes only.

Datasheet

Physical parameters	
Protection class	IP66 / IP68
Device dimensions	216×174×64 mm
ATEX Certification	II 2G Ex eb mb [ib] IIC T4 Gb II 2D Ex tb [ib] IIIC T70°C Db
Working in zones	1, 2 (gases); 21, 22 (dusts)
Electrical parameters	
Power supply	100 – 240 V AC 50/60 Hz
Power consumption max.	15 W
Environmental conditions	
Operating temperature	-20 ÷ +40 °C
Storage temperature	-20 ÷ +60 °C
Relative humidity	10% ÷ 85% RH no condensation
Construction	
Housing	stainless steel






Compatible with

HX5.EX-1.4P2 H Stainless Steel Beam Scales
HX5.EX-1 HR Stainless Steel 1-Load-Cell Platform Scales
HX5.EX-1.4P2 C Beam Scales
HX5.EX-1.4N Stainless Steel Ramp Scales
HX5.EX-1.4 C 4-Load-Cell Platform Scales
HX5.EX-1.4P H Stainless Steel Pallet Scales
HX5.EX-1.4 H/Z Stainless Steel Platform Scales, Pit Version

HX5.EX-1 C 1-Load-Cell Platform Scales
HX5.EX-1 H Waterproof Platform Scales
PUE HX5.EX Weighing Terminal
HX5.EX-1.4 H Stainless Steel 4-Load-Cell Platform Scales
HX5.EX-1.4P C Pallet Scales
Stands, wall mounting kits and mounting brackets

Device dimensions



PM01.EX